

June 8, 1843. Surveyed for Henry Vanslyke in Section 22 Town 7 Range West, as follows: Beginning at the SE corner of sd section thence S 5° 46' W 40 Chains finding 1/4 S gone thence on the same course 39.83 Ch. to the SW full Corner then returned back on sd line 39.91 1/2 chains and established the 1/4 on the East side of sd section

Black Oak 1 1/2 in. Dia. N 82 E 17 links

do 2 " " S 29 W 17 1/2 "

Hick. 22 " " N 16 3/4 E 10 3/4 "

then S 5° 40' E 19.75 3/4 Chains and established 1/4 S on the East side of sd sec. Bearing tree Gum 30 S 40 1/4 E 186 links

do 30 W 116 1/2

then went back to the 1/4 S on the East thence S 84° 40' W 79 to section line on the West found the 1/4 S there destroyed then went to the SW full Corner of sd section thence N 4 1/2° W 79.50 Chains to NW corner then returned on sd line 39.75 Ch. and re-established the 1/4 on the West side of sd section Birch 12 in. dia. S 67 1/2 E 130 links

thence 19.87 1/2 Chains towards the SW full Corner and established 1/4 S Buckeye 8 in. dia N 38 1/2 E 20 links

do 18 " " S 38 3/4 W 18 "

T. H. Carson { Chain Bearers.  
Petts {

J. C. Brown, Surveyor.

All parties concerned in the above survey legally notified.  
J. C. Brown.

June 18, 1841. Surveyed for James Elder the South East Quarter and for Charles & Stephen Hayward the N.E. Quarter of Section 12 in Township No. 6 North of Range No. 5 West Beginning at the SE corner of said section thence S 82° 10' W 79.14 Chains to the SW corner then returned on sd line 1/2 the distance and established 1/4 S on the South the original one being gone Hickory 8 in. Dia. N 9 1/2 W 132 1/2 links

do 8 " " S 7° E 45 1/2 links

Thence N 5° 45' W 79.16 Chains to 1/4 S on the North side of sd section then returned 1/2 the distance and established a corner at the NW corner of said Elders and the SW corner of aforesaid Haywards Lands per agreement of parties Bearing tree Gum 8 in. Dia. S 50° W 15 links

do 10 " " N 63 E 12 1/4 links

then went 1/2 the distance from said corner to 1/4 S on the North and established 1/4 S W. Oak 20 in. Dia. S 31 W 12 1/2 links

Poplar 4 N 8 E 57 links

then returned to the center thence East to 1/4 on East side of said section

Thomas Williams.

Charles Haywood.

+ Wm. Holt, Chain Bearers. J. C. Brown, S. of L. C.

James Chambers having lands joining those described in the above survey and in the same sec. was legally notified that said survey would take place on the day and date aforesaid.

J. C. Brown.

Aug. 21, 1845 Surveyed for Henry Van Slyke and Carpus Shaw to establish the center corner of Sec. 22, T. 7 N. R. 5 W. Ran the South line of sd sec. at 3° 10' variation and fixed the Quarter corner then ran at 5° 5' variation from the 1/4 corner to the 1/4 cor on the N. side of sd. sec. and where the line crossed a line ran E. & W. through the center of sd sec. by J. C. Brown Established the center of sd section found the N 1/4 cor witness tree standing Carpus Shaw & H. Van Slyke, agreeing to take Brown's line through the center as a part of the survey.

Witness tree Poplar 18 in. Dia. S. 7. D. E. 136 links

A Stone S 44 W

Black Locust 10 in N 19° 45' W 46 1/2 links

T. H. Carson,

Michael Erity { Chain Bearers.

F. B. Cressy, C. Surveyor Greene Co.

Dec. 23, 1845. Finished a survey between Nat. Moss, E. R. Taylor, Elias Dayhoff, Wm. G. Dayhoff, & Abram. Dayhoff in Sec. 15 ran the W line of sd sec and established the center of sd sec. by running the two open lines from quarter cor - commencing on the E 1/4 cor between E. Dayhoff and Abr. Dayhoff 20 Chains W from 1/4 cor placed a rock without a witness tree Center of sec. 15 Witness tree where the lines cross

Jack Oak 12 in. Dia. N 29° W. 47 links

do do 10 " " S 43 W 45 "

" do 16 " " N — 50 "